


internal configuration





configuración interna
descriptif intérieur



power connections

conexiones de potencia


raccordements de puissance



control module

módulo de control



module de contrôle



control connections

conexiones de control




raccordements de commande



high level alarm

alarma de nivel alto


alarme de niveau haut



overload setting (I_{max})

ajuste de sobrecarga (I_{max})


réglage de surintensité (I_{max})



Jammed impeller preventive system

sistema preventivo de bloqueo rotor (protección anti-bloqueo)

système préventif de blocage rotor (dégommage automatique)



technical specifications

especificaciones técnicas

spécifications techniques

Supply voltage	230V~ I/III or 400V~ III (according to the model) -20% +30% - 50/60Hz
Pump current range	1.5...18A - AC3
Overload setting	1.6...19.2A (alarm trip in 7 seconds)
Control mode (ON and OFF levels)	Conductive probes or float switches
Control mode for High level	Float switch
Probes: Supply voltage/Sensitivity	24V~ / 9Kohm (protected against storms transients). Wire distance: 200m. max. Min. section 0.5mm ²
Terminal blocks wiring size	10mm ² (power) 4mm ² (control)
Cable glands configuration	1xM20 (main supply) / 1xM20 (motor) / 2xM16 (control)
Protections	Overload, phase failure, over-voltage, pump wiring failure and wrong control wiring
Alarm contact	10A - 250V~
Alarm contact activation	High level
Acoustic alarm sound level	90dB
Recording information (PUMPCHECK)	Module identification number, counters resets, pump running hours, pump starts, pump alarms and last alarm tripping current
Size/Weight/IP/Temperature	240 (height) x 190 (width) x 110 (depth) / 1820g / IP66 / -10 +55°C